

SINGLE OR DOUBLE LEAF GATES							
NOM HEIGHT (H)	UPRIGHT HT (U)	FRAME HT (F)					
NOM HT INCLUDING BARBED WIRE	ACTUAL DIM	ACTUAL DIM					
7'-0"	6'-10"	5'-8 1/2"					
8'-0"	7'10"	6'-8 1/2"					
9'-0"	8'-10"	7'-8 1/2"					
10'-0"	9'-10"	8'-8 1/2"					
11'-0"	10'-10"	9'-8 1/2"					
12'-0"	11'-10"	10'-8 1/2"					
13'-0"	12'-10"	11'8 1/2"					

SINGLE LEAF GATES						
OPENING	GATE POSTS	HINGE SPACE (S)				
FACE TO FACE	SQ & RND SIZES	POST TO UPRIGHT				
3'-0" THROUGH 6'-0"	2 1/2" SQ OR 2.875" OD	FOR SQUARE & ROUND GATE POSTS: 2 1/4"				
7'-0" THROUGH 10'-0"	3" SQ OR 4" OD	FOR SQUARE & ROUND GATE POSTS: 2 1/4"				
11'-0" THROUGH 12'-0"	4" SQ OR 4" OD	FOR SQUARE & ROUND GATE POSTS: 2 1/4"				
13'-0" THROUGH 18'-0"	.6" SQ OR 6.625" OD	FOR GATE POSTS: SQ-2 1/4" RND-3 1/2"				
19'-0" THROUGH 20'-0"	8" SQ OR 8.625" OD	FOR GATE POSTS: SQ-2 1/4" RND-3 1/2"				

DOUBLE LEAF GATES						
OPENING	GATE POSTS	HINGE SPACE (S)				
FACE TO FACE	SQ & RND SIZES	POST TO UPRIGHT				
8'-0" THROUGH 12'-0"	2 1/2" SQ OR 2.875" OD	FOR SQUARE & ROUND GATE POSTS: 2 1/4"				
14'-0" THROUGH 24'-0"	3" SQ OR 4" OD	FOR SQUARE & ROUND GATE POSTS: 2 1/4"				
26'-0" THROUGH 36'-0"	6" SQ OR 6.625" OD	FOR GATE POSTS: SQ-2 1/4" RND-3 1/2"				
38'0" THROUGH 40'0"	8" SQ OR 8.625" OD	FOR GATE POSTS: SQ-2 1/4" RND-3 1/2"				

NOTE:

CENTER UPRIGHT REQUIRED ON GATE LEAVES 8'-0" & WIDER. CENTER RAIL REQUIRED ON GATE LEAVES 10'-0" & HIGHER.

TYPICAL	SWING	GA	TES	WITH	I BARBED	WIRE
DRAWN: SER	APPROVED	VBY:	1	1	1	DA7E

ENG.
REVISED 8/10

ENGINEERING DEPARTMENT

PROVED BY: 1 Jucker
CITY ENGINEER

A/4/06

F-9

CITY OF MERCED, CA.

SHEET OF