

NOTES:

- SERVICE IS NORMALLY PROVIDED MONDAY THROUGH SATURDAY, 11:00 P.M. TO 2:30 P.M. REGULAR SCHEDULED
 -SERVICE IS GIVEN PRIORITY OVER ON-CALL SERVICE. THE CITY WILL SUPPLY AND MAINTAIN 3, 6, AND 8-CUBIC YARD
 CONTAINERS ARE EMPTIED AT THE SITE.
- SERVICE ENVELOPES SHALL NOT BE IMPAIRED IN ANY WAY. DIMENSIONS ARE THE MINIMUM (CLEAR) VALUES REQUIRED FOR PROPER SERVICE.
- 3. CONTAINER ACCESS SHALL BE AT LEAST 14 FEET WIDE AND 13 FEET 6 INCHES HIGH. REFUSE VEHICLE TURN RADIUS DESIGN SHALL COMPLY WITH THE STATE HIGHWAY DESIGN MANUAL (LATEST EDITION), AND THE "BUS" TURNING TEMPLATE SHALL BE USED AS A MINIMUM. INSIDE TURN RADIUS SHALL NOT BE WITHIN THE LOADING ENVELOPE. DRIVE—THROUGH ACCESS MUST BE PROVIDED. MINIMUM HEIGHT OVER LOADING AREA IS 22 FEET 0 INCHES.
- 4. ENCLOSURE OPTIONAL UNLESS REQUIRED BY DEVELOPEMENT APPROVAL. GATES, IF ANY, SHALL BE OPENED BY CUSTOMER PRIOR TO SERVICE COLLECTION AND SHALL BE POSITIONED TO AVOID INTERFERENCE WITH SERVICE. ENCLOSURE LOCATION IS SUBJECT TO APPROVAL BY THE SOLID WASTE MANAGER.
- 5. DURING CONTAINER LOADING, FRONT WHEEL AND AXLE LOADS MAY EXCEED STREET AND HIGHWAY LIMITS. THE CITY IS NOT RESPONSIBLE FOR INADEQUATELY DESIGNED OR CONSTRUCTED PAVEMENT ON THE SITE.
- 6. ENTRANCE SHALL NOT BE RESTRICTED BY HINGES, GATES, ETC.
- 7. REFUSE DIVISION WILL CONDUCT AN ONSITE INSPECTION OF ENCLOSURE FORMS PRIOR TO CONCRETE BEING POURED.
 - * ADD 8 FEET FOR EACH ADDITIONAL REFUSE CONTAINER.

ENGINEERING DEPARTMENT		CITY OF N	MERCED, CA.
FRONT END LOADER SERVICE		R-2	
DRAWN: KGE APPROVED BY	7/17/08	1 ₹-2	
REVISED:3/17/08 CITY ENGINEER		SHEET	OF