		PEDESTRIAN ROUTE -		
	<u> </u>			ACCESSIBILITY SIGN
ALLOW 2'-6" BUMPER OVERHANG	6" CONCRETE CURB	1:12 MAX SLOPE	C DEPRESS CURB TO PROVIDE ACCESS TO PEDESTRIAN RO	
17'-6" MIN	4" STRIPE 4" STRIPE (36" O.C.)		4" STRIPE	
	9'-0" MIN			PAVEMENT SYMBOL PER NOTE 3
ł	9'-0 MIN	• •	9'-0" MIN	
•		ACCESS	MIN FOR TYP. IBLE PARKING STALL MIN FOR VAN	
			IBLE PARKING STALL	
NOTES:				
1. One	in every eight accessit	ole spaces, but	not less than one. sha	Ill be served
by	an access aisle 8' wide	minimum and	shall be designated va	accessible.
Van With	h parking space reserve ntified by a reflectorized accessible parking spa State Standard Sign R ght of 80 inches from t	sign in accorda ces shall be ide 99 and R99a.	ance with State Standa ntified by reflective sig Signs shall be posted	rd Sign R99. ns in accordance at a minimum
3. Pav See	rement symbol shall be • TC—11 for size of whe	a white wheelch elchair symbol.	air with occupant and	blue background.
4. An lot. acc for veh	additional sign (17°x22" The sign shall read a essible spaces not displ persons with disabilities icles may be reclaimed 5-6912).") shall be instal s follows: "Unau aying distinguish may be towed	ing placards or license away at owner's expe	plates issued
5. If a ar	overhang encroaches ont ninimum 4'-0" clear wi	o a pedestrian dth.	area, pedestrian area	shall have
► PAR	KING STALL SHALL BE 2	0'-0" LONG IF :	2'-6" CURB OVERHANG	IS NOT PROVIDED.
NGINEERING DEPA	RTMENT			CITY OF MERCED, CA.
HANE)ICAP STALL & (URB LOCA	ΓΙΟΝ	
RAWN: MP AF	PROVED BY:	<u> </u>	DATE	TC-8A